

Declare. SM

Carbocrylic 3359 DTMC Carboline Company

Final Assembly: Dayton, NV

Life Expectancy: Life of Structure Year(s)

End of Life Options: Landfill (100)

Ingredients:

Unnamed Material: Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Titanium dioxide; 1-(2-butoxy-1-methylethoxy)propan-2-ol; Polycarboxylic acid; 5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-; Aluminum hydroxide; Ammonium Hydroxide, NOS; Amorphous silica; Nitrous acid, sodium salt; Poly[oxy(methyl-1,2-ethanediyl)], α -hydro- ω -hydroxy-

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: 44 g/L |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

CRB-0018

EXP. 01 APR 2022

Original Issue Date: 2020