

Thermo-Sorb VOC Carboline Company

Final Assembly: Dayton, Nevada, USA

Life Expectancy: Life of Structure Year(s)

End of Life Options: Landfill (100%)

Ingredients:

1,3-Propanediol, 2,2-bis(hydroxymethyl)-; 2-Propenoic acid, 2-ethylhexyl ester, polymer with ethenylmethylbenzene;
Ammonium polyphosphate; Carbonic acid, dimethyl ester;
Acetic acid, 1,1-dimethylethyl ester; Alkanes, C18-28, chloro;
Melamine; Titanium dioxide; Toluene; 2-Hexanone, 5-methyl-;
Alkanes, C14-17, chloro; 2-Pentanone, 4-hydroxy-4-methyl-;
Aluminosilicate Refractory Ceramic Fibres; Octadecanoic acid, zinc salt; Carbon black

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free
 - LBC Red List Approved
 - Declared
- % Disclosed: 100% at 100ppm
VOC Content: 142 g/L

I-10 Interior Performance: CDPH Standard Method v1.1-2010

I-14 Responsible Sourcing: Not Applicable

CRB-0001

EXP. 01 OCT 2021

Original Issue Date: 2018