

Safety Data Sheet

<sup>®</sup> Prepared in Accordance with HCS 29 C.F.R. 1910.1200

# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	1156B1NL	Revision Date:	12/05/2022
	Product Name:	CARBOMASTIC 94 TL PART B	Supercedes Date:	12/20/2021
1.2	Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use.		
1.3	Details of the supplier of the safety data sheet			
	Manufacturer:	Carboline Global Inc. 2150 Schuetz Road St. Louis, MO USA 63146 Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645		
	Datasheet Produced by:	Schlereth, Ken - regulatory@carboline.c	om	
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US CHEMTREC +1 703 5273887 (Outside L HEALTH - Pittsburgh Poison Control 1-4	(SÌ	

# 2. Hazard Identification

# 2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2 Carcinogenicity, category 1A Flammable Liquid, category 3 Reproductive Toxicity, category 1A Skin Corrosion, category 1 Skin Sensitizer, category 1

# 2.2 Label elements

### Symbol(s) of Product



Signal Word

Danger

### Named Chemicals on Label

4,4'-ISOPROPYLIDENEDIPHENOL, PARACHLOROBENZO TRIFLUORIDE, TRIETHYLENETETRAMINE, MICROCRYSTALLINE SILICA, POLYAMIDE, BRANCHED AMINE

## HAZARD STATEMENTS

Flammable Liquid, category 3 Skin Corrosion, category 1 Skin Sensitizer, category 1 Carcinogenicity, category 1A Reproductive Toxicity, category 1A Hazardous to the aquatic environment, Chronic, category 2	H226 H314-1 H317 H350-1A H360-1A H411	Flammable liquid and vapour. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer. May damage fertility or the unborn child. Toxic to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P264	Wash hands thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P284	Wear respiratory protection.
	P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
	P301+330+331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P308+313	IF exposed or concerned: Get medical advice/attention
	P308+P313	IF exposed or concerned: Get medical advice/attention
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.
	P363	Wash contaminated clothing before reuse.
	P391	Collect spillage.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.

### 2.3 Other hazards

No Information

### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# 3. Composition/Information On Ingredients

# 3.2 Mixtures

# Hazardous ingredients

Name According to EEC	<u>EINEC No.</u> 215-279-6	<u>CAS-No.</u> 1317-65-3	<u>%</u> 10 - <25	<u>Classifications</u> H315-319	Eye Irrit. 2, Skin Irrit. 2
TALC	238-877-9	14807-96-6	10 - <25		
POLYSTYRENE	500-008-9	9003-53-6	10 - <25	H360	
POLYAMIDE	614-452-7	68410-23-1	10 - <25	H315-317-318-411	Aquatic Chronic 2, Eye Dam. 1, Skin Irrit. 2, Skin Sens. 1
ZINC PHOSPHATE	231-944-3	7779-90-0	2.5 - <10	H400-410	
PARACHLOROBENZO TRIFLUORIDE	202-681-1	98-56-6	2.5 - <10	H226-315-317-319-335	
BRANCHED AMINE	270-851-2	68479-04-9	2.5 - <10	H302-314-410	
MICA	310-127-6	12001-26-2	2.5 - <10	H319-335	Eye Irrit. 2, STOT SE 3 RTI
4,4'- ISOPROPYLIDENEDIP HENOL	201-245-8	80-05-7	2.5 - <10	H317-318-335-360F-400-410	Aquatic Acute 1, Aquatic Chronic 1, Eye Dam. 1, Repr. 1B, Skin Sens. 1, STOT SE 3 RTI
TRIETHYLENETETRA MINE	203-950-6	112-24-3	1.0 - <2.5	H302-312-314-317-412	
TRIS-2,4,6- (DIMETHYLAMINOMET HYL)PHENOL	202-013-9	90-72-2	1.0 - <2.5	H302-315-319	Acute Tox. 4 Oral, Eye Irrit. 2, Skin Irrit. 2
MICROCRYSTALLINE SILICA	238-878-4	14808-60-7	0.1 - <1.0	H350-372	Carc. 1A, STOT RE 1
ETHYL BENZENE	202-849-4	100-41-4	0.1 - <1.0	H225-304-315-319-332-351-373 -412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Carc. 2, Eye Irrit. 2, Flam. Liq. 2, Skin Irrit. 2, STOT RE 2

CAS-No.	M-Factors
1317-65-3	0
14807-96-6	0
9003-53-6	0
68410-23-1	0
7779-90-0	0
98-56-6	0
68479-04-9	0
12001-26-2	0
80-05-7	0
112-24-3	0
90-72-2	0
14808-60-7	0
100-41-4	0

Additional Information:

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

### 4.1 Description of First Aid Measures

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

# 5. Fire-fighting Measures

# 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

FOR SAFETY REASONS NOT TO BE USED: No Information

#### 5.2 Special hazards arising from the substance or mixture No Information

No Information

### 5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

# 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear self-contained breathing apparatus and protective suit. Wear suitable gloves and eye/face protection. Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

No Information

# 7. Handling and Storage

# 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING :** Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

**PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Heat, flames and sparks. **STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

### 7.3 Specific end use(s)

No specific advice for end use available.

# 8. Exposure Controls/Personal Protection

# 8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
LIMESTONE	1317-65-3	N/E	N/E	N/E
TALC	14807-96-6	2 MGM3	N/E	N/E
POLYSTYRENE	9003-53-6	N/E	N/E	N/E
POLYAMIDE	68410-23-1	N/E	N/E	N/E
ZINC PHOSPHATE	7779-90-0	N/E	N/E	N/E
PARACHLOROBENZO TRIFLUORIDE	98-56-6	N/E	N/E	N/E
BRANCHED AMINE	68479-04-9	N/E	N/E	N/E
MICA	12001-26-2	3 MGM3	N/E	N/E
4,4'-ISOPROPYLIDENEDIPHENOL	80-05-7	N/E	N/E	N/E
TRIETHYLENETETRAMINE	112-24-3	N/E	N/E	N/E
TRIS-2,4,6- (DIMETHYLAMINOMETHYL) PHENOL	90-72-2	N/E	N/E	N/E
MICROCRYSTALLINE SILICA	14808-60-7	0.025 MGM3	N/E	N/E
ETHYL BENZENE	100-41-4	20 PPM	125 ppm	
Name	CAS-No.	<u>OSHA PE</u>	<u>IL OSHA</u>	<u>STEL</u>
LIMESTONE	1317-65-3	5 MGM3 15 M MGM3 15 M MGM3 15 M	GM3 5 N/	E
TALC	14807-96-6	0.1 MGM3	N/	E
POLYSTYRENE	9003-53-6	N/E	N/	E
POLYAMIDE	68410-23-1	N/E	N/	E
ZINC PHOSPHATE	7779-90-0	N/E	N/	E

PARACHLOROBENZO TRIFLUORIDE	98-56-6	N/E	N/E
BRANCHED AMINE	68479-04-9	N/E	N/E
MICA	12001-26-2	20. MPPCF	N/E
4,4'-ISOPROPYLIDENEDIPHENOL	80-05-7	N/E	N/E
TRIETHYLENETETRAMINE	112-24-3	N/E	N/E
TRIS-2,4,6- (DIMETHYLAMINOMETHYL) PHENOL	90-72-2	N/E	N/E
MICROCRYSTALLINE SILICA	14808-60-7	0.05 MGM3	N/E
ETHYL BENZENE	100-41-4	435 MGM3, 100 PP <b>54</b> 5	MGM3, 125 PPM

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

# 9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	Viscous Liquid
	Physical State	Liquid
	Odor	Solvent
	Odor threshold	N/D
	рН	N/D
	Melting point / freezing point (°C)	N/D
	Boiling point/range (°C)	176 F (80 C) - 531 F (277 C)
	Flash Point (°C)	105°F (40°C)
	Evaporation rate	Slower Than Ether
	Flammability (solid, gas)	Not determined
	Upper/lower flammability or explosive limits	0.9 - 17.4
	Vapour Pressure, mmHg	

		N/D
	Vapour density	Heavier than Air
	Relative density	Not determined
	Solubility in / Miscibility with water	N/D
	Partition coefficient: n-octanol/water	Not determined
	Auto-ignition temperature (°C)	Not determined
	Decomposition temperature (°C)	Not determined
	Viscosity	Unknown
	Explosive properties	Not determined
	Oxidising properties	Not determined
9.2	Other information	
	VOC Content g/l:	95
	Specific Gravity (g/cm3)	1.53

# 10. Stability and Reactivity

### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

**10.2 Chemical stability** Stable under normal conditions.

# 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

### 10.4 Conditions to avoid

Heat, flames and sparks.

### **10.5 Incompatible materials** Strong oxidizing agents.

### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

	0		
11.1	Information on toxicological effects		
	Acute Toxicity:		
	Oral LD50:	N/D	
Inhalation LC50:N/DIrritation:UnknownCorrosivity:Skin Corrosion, category 1Sensitization:Skin Sensitizer, category 1Repeated dose toxicity:UnknownCarcinogenicity:Carcinogenicity, category 1AMutagenicity:UnknownToxicity for reproduction:Reproductive Toxicity, category 1ASTOT-single exposure:No Information		N/D	
		Unknown	
		Skin Corrosion, category 1	
		Skin Sensitizer, category 1	
		Unknown	
		Carcinogenicity, category 1A	
		Unknown	
		Reproductive Toxicity, category 1A	
		No Information	
	STOT-repeated exposure:	No Information	
	Aspiration hazard:	No Information	

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	<u>Oral LD50</u>	Dermal LD50	Vapor LC50	Gas LC50	<u>Dust/Mist</u> LC50
1317-65-3	LIMESTONE	Not Available	Not Available	5,000 mg/kg, rat, oral	0.000	0.000
14807-96-6	TALC	Not Available		Not Available	0.000	0.000
9003-53-6	POLYSTYRENE	Not Available		Not Available	0.000	0.000
68410-23-1	POLYAMIDE	>5000 mg/kg, oral, rat		Not Available		
7779-90-0	ZINC PHOSPHATE	3846mg/kg, oral rat	Not Available	Not Available	0.000	11.54 mg/l
98-56-6	PARACHLOROBENZO TRIFLUORIDE	6800 mg/kg, oral, rat	3300 mg/kg, dermal, rabbit	4479 ppm	0.000	0.000
12001-26-2	MICA	Not Available	Not Available	Not Available	0.000	0.000
80-05-7	4,4'- ISOPROPYLIDENEDIPHENOL	11400 mg/kg, oral, rat	Not Available	Not Available	0.000	0.000
112-24-3	TRIETHYLENETETRAMINE	1716 mg/kg rat, oral	1465 mg/kg, dermal, rabbit	Not Available		
90-72-2	TRIS-2,4,6- (DIMETHYLAMINOMETHYL) PHENOL	1999 mg/kg (rat)	Not Available	Not Available	0.000	0.000

14808-60-7	MICROCRYSTALLINE SILICA	22500 mg/kg	Not Available	Not Available	0.000	0.000
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr	0.000	0.000

### Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form or progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other silicates as impurities, and above dei minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

# 12. Ecological Information

12.1 Toxicity:

	EC50 48hr (Daphnia): IC50 72hr (Algae): LC50 96hr (fish):	Unknown Unknown Unknown
12.2	Persistence and degradability:	Unknown
12.3	Bioaccumulative potential:	Unknown
12.4	Mobility in soil:	Unknown
12.5	Results of PBT and vPvB assessment:	The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects:

Unknown

CAS-No.	Chemical Name	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
1317-65-3	LIMESTONE	1,000 mg/l	200 mg/l	10,000 mg/l
14807-96-6	TALC	No information	No information	No information
9003-53-6	POLYSTYRENE	No information	No information	No information
68410-23-1	POLYAMIDE	No information	No information	No information
7779-90-0	ZINC PHOSPHATE	0.04 - 0.86 mg/l (Daphnia Magna)	0.136 - 0.150 mg/l (Selenastrum capricornutum)	0.14 - 0.26 mg/l (Rainbow Trout)
98-56-6	PARACHLOROBENZO TRIFLUORIDE	2 mg/l (Daphnia magna)	No information	3 mg/l (Zebra fish)
68479-04-9	BRANCHED AMINE	No information	No information	No information
12001-26-2	MICA	No information	No information	No information
80-05-7	4,4'-ISOPROPYLIDENEDIPHENOL	No information	No information	No information
112-24-3	TRIETHYLENETETRAMINE	No information	No information	No information
90-72-2	TRIS-2,4,6- (DIMETHYLAMINOMETHYL) PHENOL	No information	84 mg/l (Algae)	175 mg/l (Fish)
14808-60-7	MICROCRYSTALLINE SILICA	No information	No information	No information
100-41-4	ETHYL BENZENE	1.8 mg/l (Daphnia Magna)	4.6 mg/l (Green Algae)	4.2 mg/l (Rainbow Trout)

# 13. Disposal Considerations

**13.1** WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport Information

14.1	UN number	UN 1263
14.2	UN proper shipping name	Paint
	Technical name	N/A
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	N/A
14.4	Packing group	111
14.5	Environmental hazards	Unknown
14.6	Special precautions for user	Unknown
	EmS-No.:	F-E, S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

# 15. Regulatory Information

<sup>15.1</sup> Safety, health and environmental regulations/legislation for the substance or mixture:

# U.S. Federal Regulations: As follows -

### **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Reproductive toxicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization

### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

CAS-No.	<u>%</u>
7779-90-0	7.83
80-05-7	3.2
100-41-4	0.17
	7779-90-0 80-05-7

### **Toxic Substances Control Act:**

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
PARACHLOROBENZO TRIFLUORIDE	98-56-6
J.S. State Regulations: As follows -	

### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

### Chemical Name

ι

### CAS-No.

# No NJ Right-To-Know components exist in this product.

### Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product. CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

# International Regulations: As follows -

# \* Canadian DSL:

All chemical ingredients included on inventory (DSL)

### 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# 16. Other Information

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H360F	May damage fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Reasons for revision

### No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.