

Thermo-Sorb VOC Carboline Global, Inc.

Final Assembly: Dayton, Nevada, USA Life Expectancy: Life of Structure Year(s) Embodied Carbon: 8.25E+01 kg CO₂ Declared Unit: One Square Meter

End of Life Options: Landfill (100%)

Ingredients:

1,3-Propanediol, 2,2-bis(hydroxymethyl)-; 2-Propenoic acid, 2-ethylhexyl ester, polymer with ethenylmethylbenzene; Ammonium polyphosphate; Carbonic acid, dimethyl ester; Acetic acid, 1,1-dimethylethyl ester; Alkanes, C18-28, chloro; Melamine; Titanium dioxide; Toluene; 2-Hexanone, 5-methyl-; Alkanes, C14-17, chloro; 2-Pentanone, 4-hydroxy-4-methyl-; Aluminosilicate Refractory Ceramic Fibres; Octadecanoic acid, zinc salt; Carbon black

Living Building Challenge Criteria: Compliant

I-13 Red List:

■ LBC Red List Free

☐ LBC Red List Approved

□ Declared

% Disclosed: 100% at 100ppm

VOC Content: 142 g/L

I-10 Interior Performance: CDPH Standard Method v1.2-2017
I-14 Responsible Sourcing: Not Applicable

CRB-0001 EXP. 01 MAR 2025 Original Issue Date: 2018